



# Fluidpro Custom Cylinders

GIVE GENERAL DESCRIPTION OF THE MACHINE OR APPLICATION USING THE CYLINDER. SUPPLY ANY ADDITIONAL INFORMATION IF POSSIBLE.

BORE DIA.	_____	(MOUNTING ARRANGEMENT)		BORE	A	B	C	D	E	PORTS
ROD DIA.	_____	1. PINNED ENDS-DIA. OF PIN _____ IN.		2.5	2.75	1.625	1	1.875	3	-6
STROKE INCHES	_____	LENGTH OF CONNECTION _____ IN.		3.5	2.5	2.31	1.25	2.56	4	-8
ROD EXTENSION (MIN. 1 IN.)	_____	2. TRUNNION MOUNT		4	3.13	2.56	1.5	2.56	4.5	-10
OPERATING PRESSURE P.S.I.	_____	DIAMETER OF TRUNNION _____ IN.		4.5	3.25	2.585	1.655	2.562	5	-10
TEST PRESSURE P.S.I.	_____	LENGTH OF TRUNNION _____ IN.		5	3.523	2.813	1.875	3	5.75	-12
OPERATING FLUID	_____	LOCATION OF TRUNNION _____ IN.		5.5						-12
MAX. OPERATING TEMP. F*	_____	FROM ROD END _____ IN.		6	4.563	3.375	2	3.375	6.75	-12
SPECIAL ROD MAT'L.	_____	TYPE AND SIZE OF LOAD _____ LBS.		8						-16
SPECIAL SEAL MAT'L	_____	DIRECTION OF LOAD _____ PUSH _____ PULL		9	6.75	5.13	2.75	5.69	11	-16
		(SPECIAL FEATURES)		<b>KANAMAK HYDRAULICS INC.</b> 2218 W MARY ST GARDEN CITY, KS 67846 WWW.KANAMAK.COM Tel: (620) 275-6055 800-47-FLUID Fax: (620) 275-0120 <b>(PLEASE FAX FOR QUOTE)</b>						
		1. INTEGRAL VALVE. _____ .								
		2. SPECIAL PORTS. _____ YES _____ NO IF SPECIAL. PORT TYPE. _____ . PORT SIZE _____ .								